

Stretta Aya UP

Data Sheet

Made for
 iPhone | iPad | iPod



Earhook


- 82 dB / 140 dB SPL
(2 ccm coupler)
- 85 dB / 143 dB SPL
(Ear simulator)

Stretta Aya UP | Technical Data

Type	Earhook	
	2 ccm coupler	Ear simulator
Output sound pressure level		
OSPL 90 at 1.6 kHz	–	134 dB SPL
OSPL 90 (peak)	140 dB SPL	143 dB SPL
HFA-OSPL 90	132 dB SPL	–
Gain		
FOG at 1.6 kHz	–	77 dB
FOG (peak)	82 dB	85 dB
HFA-FOG	74 dB	–
Reference test gain	55 dB	59 dB
Frequency, noise and directivity		
Frequency range	100 – 5300 Hz	100 – 5400 Hz
Equivalent input noise	16 dB SPL	17 dB SPL
Total harmonic distortion at 500 / 800 / 1600 / 3200 Hz	5 / 1 / 1 / 1 %	5 / 1 / 1 / – %
Tinnitus Function broadband	94 dB SPL	–
AI-DI	3.8 dB	
Inductive coil sensitivity		
MASL (1 mA/m) at 1.6 kHz	–	105 dB SPL
HFA MASL (1 mA/m)	103 dB SPL	–
HFA SPLITS (left/right)	114 / 114 dB SPL	–
RSETS (left/right)	-1 / -1 dB	–
HFA SPLIV	115 dB SPL	–
Battery		
Battery voltage	1.3 V	
Battery current drain	2.2 mA	1.8 mA
Battery runtime (without streaming)	up to 277 h	
Battery runtime (incl. 60 h streaming)	up to 217 h	
Cellphone Compatibility		
Microphone mode	0.65 – 0.96 GHz 1.4 – 2.7 GHz	
Telecoil mode	0.65 – 0.96 GHz 1.4 – 2.7 GHz	


Please find additional information to the values on page “Further information”.

Stretta Aya UP | Fitting Range




Earhook | Basic Data

2 ccm coupler




Max. Output sound pressure level
($L_1 = 90$ dB)

Full on gain
($L_1 = 50$ dB)




Frequency response
($L_1 = 60$ dB)

Ear simulator




Max. Output sound pressure level
($L_1 = 90$ dB)

Full on gain
($L_1 = 50$ dB)




Basic acoustic response
($L_1 = 60$ dB)

Inductive response




Inductive response
($H = 10$ mA/m)



SPLITS curve left
($H = 31.6$ mA/m)

SPLITS curve right
($H = 31.6$ mA/m)



SPLIV curve
($H = 31.6$ mA/m)

Stretta Aya UP | Features and Accessories

Dynamic Soundscape Processing 2.0	■ ■ ■ ■ ■
Augmented Focus	✓
Acoustic Sensor	✓
Motion Sensor	—
OVP 2.0 (Own Voice Processing) ¹⁾	✓
Sound Clarity	■ ■ ■ ■ ■
Signal processing (channels) / Gain&MPO (handles)	32 / 16
Hearing programs	6
Extended dynamic range	✓
Speech and noise management	✓
SoundSmoothing	✓
Feedback cancellation	✓
HD Music (presets)	3
eWindScreen	✓
Extended bandwidth	—
Auto EchoShield	—
EchoShield	✓
Speech Quality	■ ■ ■ ■ ■
Binaural Directionality	✓
Wireless CROS/BICROS	✓
Frequency compression	✓
Spatial SpeechFocus ^{1) 2)}	✓
Wearer Interaction	■ ■ ■ ■ ■ ■
Signia Assistant	✓
Signia App (iOS and Android)	✓
Adaptive Streaming Volume ³⁾	✓
Spatial Configurator	✓
Direct Streaming	✓
Android devices (ASHA)	✓
Made for iPhone iPad iPod	✓
HandsFree for iOS	—
Tinnitus	✓
Notched Amplification Therapy	—
Tinnitus noise therapy signal	✓
Fitting	✓
Smart Optimizer and Data Logging	✓
Acclimatization manager	✓
InSituGram	✓
AutoFit	✓
TeleCare	✓
Remote Services	✓
Signia App	✓

¹⁾ req. bilateral fitting

²⁾ right/left directionality available only in Stroll Program and via the Spatial Configurator

³⁾ streaming only

■ ■ ■ ■ ■ highest feature performance

✓ available — not available ○ optional

Stretta Aya UP | Features and Accessories

Type specific features	
Ingress Protection Rating	IP68
Charging contacts	—
Battery size	675
Battery door on/off function	✓
Nanocoated housing	✓
e2e wireless 4.0	✓
User controls coupling via e2e	✓
Wireless programming	✓
Instrument configurations	
Flat cover	—
Rotary volume control	—
Push button	—
Rocker switch	✓
Color conversion kit	○
Color conversion kit with T-Coil	—
T-Coil	✓
Battery door – tamper proof	○
Small earhook	○
Programming accessories	
ConnexxAir / ConnexxLink	— / —
Noahlink Wireless	mandatory
Programming adapter / cable	—
Accessories	
miniPocket	○
StreamLine TV	○
StreamLine Mic	○
CROS Pure C&G AX	○
CROS Pure 312 AX	○
CROS Styletto AX	—

✓ available — not available ○ optional

Stretta Aya UP | Further information

Abbreviations

The following abbreviations are used in this datasheet:

SPL	Sound Pressure Level
OSPL	Output Sound Pressure Level
HFA	High Frequency Average
FOG	Full-On Gain
MASL	Magneto Acoustical Sensitivity Level
SPLITS	Coupler SPL for an Inductive Telephone Simulator
RSETS	Relative Simulated Equivalent Telephone Sensitivity
SPLIV	SPL In a Vertical magnetic field
AI-DI	Articulation Index - Directivity Index
IRIL	Input Related Interference Level
RTF	Reference Test Frequency
ASHA	Audio streaming for hearing aids


Standards and additional information

- All measurements with the 2 ccm coupler were performed according to ANSI S3.22-2014 and IEC 60118-0:2015 if applicable.
- All measurements with an ear simulator were performed according to IEC 60118-0:1983 + A1:1994 and to DIN 45605 (frequency range) if applicable.
- All Cellphone Compatibility measurements were performed according to IEC 60118-13:2019, EN IEC 60118-13:2020 and ANSI C63.19-2019.
- Cellphone Compatibility definition: It is expected that the hearing aid user can effectively use a compliant wireless device held in a talking position at the ear. Maximum achievable Cellphone Compatibility range: 0.65–0.96 GHz and 1.4–2.7 GHz.
- Curves and figures representing FOG are measured with 20 dB reduction and 70 dB SPL input level.
- Figures representing Equivalent Input Noise incorporate a moderate expansion.
- Tinnitus noiser measurement conditions: all tinnitus single frequency sliders in max position, master volume slider in default position (0 dB) and local volume control in default position.
- Inductive coil sensitivity values, inductive response curves and T ratings apply for instruments with telecoil only.
- The current consumption is measured in reference test setting (RTS) according to the applicable standards. Due to the settling behaviour of hearing aids supporting RF (radio frequency), the battery current is measured 3 minutes after turning on (note: no pairing).
- The battery runtime is based on first fit settings using 80 % of the fitting range and an ISTS (International Speech Test Signal) input signal at 65 dB SPL (note: pairing established). The actual battery runtime is determined by battery quality, hearing loss, sound environment, usage and activated feature set. Regarding RF usage, Bluetooth audio streaming from phone to hearing aid and from hearing aid to phone are considered.
- The following acoustic connections/ear pieces were used:
 - Earhook



“Made for iPhone”, “Made for iPad”, and “Made for iPod” mean that an electronic accessory has been designed to connect specifically to iPhone, iPad, or iPod, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPhone, iPad, or iPod may affect wireless performance.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice. The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.

 **Legal Manufacturer**
WSAUD A/S
Nymøllevej 6
3540 Lynge
Denmark


0123

Order No. 05194-99T01-7600
© 07.2022, WSAUD A/S
All rights reserved

Subject to change
without prior notice



WARNING

Choking hazard posed by small parts.

- ▶ This instrument is not intended for the fitting of infants, children under 3 years or persons of mental incapacity.



WARNING

Instrument has an output sound pressure level of 132 dB SPL or more. Risk of impairing the residual hearing of the user.

- ▶ Take special care when fitting this instrument.